

Ficha Técnica: 25/06/2020

62250051000: MXH 205/B

FICHA DE BOMBA Y MOTOR


n (rpm):	2800	Fases de motor:	3~
Max presión de trabajo (bar):	8	Un (V):	230/400
H max (m):	53.50	fq (Hz):	50
H min (m):	19.00	Polos:	2
Q min (mc/h):	1.00	In (A):	3.5 / 2
Q max (mc/h):	4.80	cosf:	0.80
Pn (kW):	0.75	Min temperatura de líquido (°C):	-15.00 °C
Pn (HP):	1.00	Peso (kg):	12.850
Diámetro de rodetes (mm):	98.00		

MATERIALES

Cuerpo bomba:	Cr-Ni steel 1.4301 EN 10088 (AISI 304)	Anillo cierre:	PTFE
Tapa del cuerpo:	Cr-Ni steel 1.4301 EN 10088 (AISI 304)	Manguito distanciador:	Cr-Ni steel 1.4301 EN 10088 (AISI 304)
Cuerpo elemento:	Cr-Ni steel 1.4301 EN 10088 (AISI 304)	Eje:	Cr-Ni steel 1.4305 EN 10088 (AISI 303)
Rodete:	Cr-Ni steel 1.4301 EN 10088 (AISI 304)	Sello mecánico:	Ceramic Alumina-Carbon-EPDM

Ficha Técnica: 25/06/2020

62250051000: MXH 205/B



Ficha Técnica: 25/06/2020

62250051000: MXH 205/B

DIMENSIONES (MM)

dn1: G 1 ¼
dn2: G 1
a: 142.00 mm
m1: 28.00 mm
m3: 8.00 mm
n1: 146.00 mm
n2: 112.00 mm
b: 30.00 mm
fM: 405.00 mm
l5: 160
g1: 10.00 mm
h1: 127.00 mm
h2: 57.00 mm
HD: 193.00 mm
w: 88.00 mm
w1: 112.00 mm

